Hydrocarbon Removal Pad

Each Mycelx Smartpad™ is capable of removing over 2 lb. of oil. Smartpad's™ unique design serves to protect surfaces and can be used to remediate oil in water or land based applications. Versatility and buoyancy make Smartpad™ effective in protecting surfaces from shop floors to sump pumps. Smartpad™ will not let oil pass through its durable shell so surfaces beneath the pad remain clean.

Benefits

- Non-shredding, durable

- Protects surfaces, will not bleed through

- Buoyant / will last indefinitely

- Prevents weathering and separation on contact

- Smartpad™ is triboelectrically inactive and will not generate static charge

- Environmentally safe

The Smartpad™ is a multi-functional oil sorbent pad. The unique design of the Smartpad™ allows it to absorb oil without letting the oil pass through its durable shell so surfaces beneath the pad remain clean. Smartpad™ will not tear or disintegrate even under the harshest usage conditions. The unique properties and unsurpassed strength of Smartpad™ make it the premier product for protecting surfaces varying from shop floors to ship bilges.

Usage Directions

Leaking Equipment
1. Place over contaminated area or position under dripping equipment to catch oil
2. Allow pad to absorb oil
3. Smartpad™ will not bleed through so surfaces beneath the pad remain clean
4. Fold Smartpad™ in half for extra usage once one side has become saturated
5. Remove and replace Smartpad™ when it is fully saturated

Dripping Fittings
1. Wrap Smartpad™ around dripping or leaking fittings to contain oil seepage
2. Remove and replace Smartpad™ when it is fully saturated

Bulk Oil Sorption
1. Place pad over contaminated area and allow to saturate with oil
2. The highly buoyant Smartpad™ will keep even heavy oil floating indefinitely